

BinMaker® PRO FAQ & Tips

Weather Data for Engineering

Some frequently asked questions and tips from BinMaker® PRO users and developer team. Have something to add? Report a problem by sending your question to binmakersupport@gti.energy

1. Find ASHRAE design conditions using BinMaker® PRO Interactive ASHRAE Design Data Viewer.

In 1997, ASHRAE revised and expanded their design weather data for the first time in over 30 years. That information now appears in BinMaker® PRO through a license agreement with the society. Because the data is in electronic form, you get more information than is possible in any printed edition. Our interactive data viewer lets you convert and display values between different units with the click of a mouse.

Access the viewer from the BinMaker® PRO opening screen by clicking the "ASHRAE Design Values" button. Then with the viewer screen visible choose the country, state/province and station location using the drop down boxes to the left. The complete set of ASHRAE data for that particular location is immediately displayed. Want a particular location displayed each time the viewer starts? Just go to that location and click "Save Location"

Click the "English (I-P)" or "Metric (SI)" options to specify the units of measure for the display. You can even turn sections of the display on/off by clicking the radio buttons labeled "Cooling", "Wind" or "Heating". Save these settings by clicking the "Default" button.

Not sure what all the data labels mean? Use a right mouse click over a label (for example DB / MCWB) and a brief explanation is displayed at the top of the screen. Need more Help? The data viewer is fully supported by an indepth help file, click the "Help" button.

2. Use Joint Frequency Table (JFT) output to better understand weather.

A joint frequency table summarizes the hourly observations in a matrix, with

columns of temperature and rows of moisture. Each observation is added to the cell at the combination of temperature and moisture that occurred during that hour. Visually, the resulting table looks like an overlay for a psychometric chart, with hour-counts appearing at the intersection of major divisions of temperature and moisture. You can view these coincident values of temperature and humidity ratio easily in a spreadsheet program.

At the final screen use the "Save" button to save the JFT in tab delimited format. Open the saved file in your spreadsheet program.

Select the range of data in the table to plot.

Use a 3D plotting method (3D-Surface works great) to display the data.

If necessary, rotate the graph to represent a typical psychometric chart layout.

The graph depicts the total hours of occurrence for each of the coincident values of temperature and humidity ratio. Viewing the data in this manner gives a better understanding about the periods of time associated with each temperature and humidity ratio combination for the specific application data that you have entered. For some engineers this has provoked thoughts about checking their designs against the conditions that relatively frequently as well as the project design conditions.

3. Checking binned output values from BinMaker® PRO.

BinMaker® PRO uses standard calculation procedures published by many engineering references including the ASHRAE Handbook of Fundamentals. However checking the binned output from BinMaker® PRO requires some thought about how the calculations are performed within the program.

Here are a few tips:

- Be certain your psychometric conversion utility yields accurate results.
- Keep in mind that the TMY2 data includes the atmospheric pressure for each hour. BinMaker® PRO uses each hour's pressure to calculate psychometric properties beyond those in the TMY2 data set.
- Use standard procedures for calculating loads.
- For a thorough check start with a single hour. Then increase the time period to see how the binning process works.

- You may even find it advantageous to down the full TMY2 dry bulb temperature, dew point temperature and atmospheric pressure so you can replicate the process completely.

4. BinMaker® PRO psychometric calculations.

BinMaker® PRO uses dry bulb, dew point and atmospheric pressure values from TMY2 data sets. Using these values wet bulb temperature, humidity ratio and enthalpy are calculated. These calculations are carried out for each hour's data prior to the binning process.

5. How to find VLIs using BinMaker® PRO.

Using BinMaker® PRO it is easy to generate new Ventilation Load Indexes (VLI) for a particular location and application. The VLI is a convenient way to compare the relative sensible and latent loads for a particular application. See the article "Dehumidification and Cooling Loads from Ventilation Air", ASHRAE Journal, November 1997, page 37 for details on Ventilation Load Index.

Use the "Preconditioning Bins" procedure, (see the user manual for details).

Set the hour schedule and inside set points for your application.

BinMaker® PRO produces the sensible and the latent VLIs and displays them graphically at the top of the final screen.

6. Special offer for registered users of BinMaker® PRO

Linric Company is offering its popular psychometric function Add-In for Excel, PsyFunc, at a 20% discount for registered users of BinMaker® PRO. Register now to take advantage of this special offer while it lasts!

With PsyFunc installed you can easily find the psychometric property you need. PsyFunc includes 38 functions that are as easily accessible as any standard Excel function. If you are using BinMaker's output in an Excel worksheet you'll find this package to be a big time saver. (PsyFunc works with Excel 5.0 or higher.)

To take advantage of this offer you will need to print the order form, complete it and fax it to Linric Company. Use only the order form from this site to get this special

pricing. If you have trouble printing the form e-mail your fax number to BinMaker support and we'll fax you one.

To learn more about the PsyFunc product visit the [Linric Company](#) site.

7. TMY2 Weather Data.

TMY2 Weather Data The TMY2 data set was constructed by the National Renewable Energy Laboratory (NREL) in Golden, Colorado, working under the direction, and with funding provided by, the United States Department of Energy.

The data has many advantages over other sets of hourly records, including:

- ***239 locations*** As of January 1998, there is no other "typical weather" data set which contains this number of locations for the United States (or even one quarter of that number).
- ***Documented, repeatable methodology*** Other data sets were constructed with one-time efforts, involving site-by-site judgments by climatologists on what should be included as "typical" weather behavior. While this has the advantage of involving expert human judgment in the process, it is difficult to reconstruct a similarly expert record for other locations. Also, equally-qualified experts often disagree on what constitutes "typical" weather. The TMY2 methodology has numerically-documented assumptions, so it can be used by different experts with repeatable results.
- ***TMY2 Methodology.*** The techniques used to construct the TMY2 data set are documented in NREL publication #NREL/SP-463-7668, published in June, 1995 and available through the National Technical Information Service, or from NREL directly. The complete text of that manual is also contained on the BinMaker® PRO CD-ROM as an Adobe PDF file. That file can be browsed and searched with the freely-distributed "Acrobat Reader ® " utility from Adobe Systems, which is also included on the BinMaker® PRO CD-ROM.
- ***Determination of "Typical Months"*** To construct a typical year, the TMY2 methodology begins by grouping like months from a long-term record. The months are compared to each other to determine which year produced the "most typical" of each month group. (e.g.: the "most typical" January, the "most typical" February, etc.)

8 What city TMY2 weather data files are included with BinMaker® PRO?

239 US locations are included. There is a list of locations at the end of this document.

9. TMY3 Weather Data.

View User Manual for TMY3 Data Sets_ for description on TMY3 data sets.

10. What city TMY3 weather data files are included with BinMaker® PRO?

1020 US locations are included. View User Manual for TMY3 Data Sets in Appendix A for complete list.

11. What weather data are available from the BinMaker® PRO data sets?

Complete weather sets can be downloaded that include 8,760 hourly records with 23 different weather fields. Twenty of the fields are directly from the TMY2/TMY3 data set. Three fields are calculated from TYM2 /TMY3 values using very precise psychometric functions. View the complete list of values and definitions at the end of this document.

12. BinMaker® PRO cannot find the BinMaker CD

The BinMaker® PRO needs to be able to locate the BinMaker CD so that it can download weather data for binning. This may be set manually or you may allow the program to search for the CD each time the program starts. To select one of these two options do the following

Start BinMaker® PRO

Click the "TMY-@ Hourly Records" button on the splash screen.

Choose "Configure" then "CD Drive Letter" from the menu.

Click the option you wish to use for specifying the CD drive letter.

If "Specify CD Location" is chosen, use the drop down box to select the CD drive letter.

Click OK.

13. How to run BinMaker® PRO version 2.1 or earlier without BinMaker CD?

- 1) Copy the data folder BMPRODATA from CD on your hard drive C.
For example, copy the data to C:\Program Files\BMPro\BMPRODATA
- 2) Go to subfolder C:\Program Files\BMPro\BMPRODATA\IP to delete file Weather.BMD, if it is there; Also go to subfolder C:\Program Files\BMPro\BMPRODATA\SI to delete file Weather.BMD, if it is.
- 3) Run the program
- 4) Click on menu button Configuration | CD Drive Letter to select the option of Specify CD Location, and select the Drives C; and Click OK
- 5) Click on menu button Configuration | Location of Data Files to set the data path as
C:\Program Files\BMPro\BMPRODATA\IP, if you run with English IP unit, or C:\Program Files\BMPro\BMPRODATA\SI, with SI unit.
*Do not forget the subdirectory IP or SI.
- 6) Click OK

Then you should be free from the DATA CD

14. How to run BinMaker® PRO version 3.0 without BinMaker CD?

- 1) Copy the data folder BMPRODATA from CD on your hard drive C, as
C:\BMPRODATA
- 2) Run the program
- 3) Click on menu button Configuration | CD Drive Letter to select the option of Specify CD Location, and select the Drives C; and Click OK
- 4) Click on menu button Configuration | Location of Data Files to set the data path as
C:\BMPRODATA
- 5) Click OK

Then you should be free from the DATA CD

15. How to transfer the license from a licensed computer to a new computer?

Software license for unlimited use of the product on single computer can be

transferred from another licensed computer. After transferring the license to new computer, you will not be able to use/run the program on the old computer.

Therefore, please make sure that is what you want before transferring the license. If you would like to run program on both computers you need to buy a new license.

To transfer the license from old to new computer, please do the following

· New computer you are transferring license to.

- 1) Install the software on your new computer.
- 2) Run the software. When the initial form appears on the new computer, click Transfer License button.
- 3) Insert a floppy disk (a license transfer disk) into drive A* of this computer.
- 4) Click Start Transfer button to initiate the license transfer process.
- 5) When finished, remove the disk from the new computer.

· Old computer, which has original license.

- 1) Run the program on your old computer.
- 2) Put the license transfer disk with an initiation file created from the new computer into drive A* of this computer.
- 3) Click on the Transfer License via File pull-down menu at the top of main screen.
- 4) After the transferred license file is copied to the disk, take the disk out.

Now, the license on the old computer is disabled. You should uninstall the software from this machine.

· Go back to the new computer.

- 1) Put the license transfer disk back to the new computer drive A*.
- 2) Click on the Activate Transferred License button to finish the transfer process.

The license should be now transferred to the new computer. The program will stop running after the license is transferred. Just re-start the program.

*Note: The program uses the drive A as the default floppy /disk drive of computers.

If your computer does not have a floppy disk drive, please use the menu button of Select Floppy / Disk Drive to select any drives of the devices with removable storages (CD re-writable, USB flash memory, or others.).

TMY2/TMY3 Data Descriptions:

Extraterrestrial Horizontal Radiation

Amount of solar radiation in Wh/m² or BTU's/ft² received on a horizontal surface at the top of the atmosphere during the 60 minutes preceding the hour indicated.

Extraterrestrial Direct Normal Radiation

Amount of solar radiation in Wh/m² or BTU's/ft² received on a surface normal to the sun at the top of the atmosphere during the 60 minutes preceding the hour indicated.

Global Horizontal Radiation

Total amount of direct and diffuse solar radiation in Wh/m² or BTU's/ft² received on a horizontal surface during the 60 minutes preceding the hour indicated.

Direct Normal Radiation

Amount of solar radiation in Wh/m² or BTU's/ft² received within a 5.7 deg. field of view centered on the sun during the 60 minutes preceding the hour indicated.

Diffuse Horizontal Radiation

Amount of solar radiation in Wh/m² or BTU's/ft² received from the sky (excluding the solar disk) on a horizontal surface during the 60 minutes preceding the hour indicated.

Global Horizontal Illuminance

Average total amount of direct and diffuse illuminance in hundreds of lux or foot-candles received on a horizontal surface during the 60 minutes preceding the hour indicated.

Direct Normal Illuminance

Amount of direct normal illuminance in hundreds of lux or foot-candles received within a 5.7 deg. field of view centered on the sun during the 60 minutes preceding the hour indicated.

Diffuse Horizontal Illuminance

Average amount of illuminance in hundreds of lux or foot-candles received from the sky (excluding the solar disk) on a horizontal surface during the 60 minutes preceding the hour indicated.

Zenith Luminance

Average amount of luminance at the sky's zenith in tens of footlamberts or Cd/m² during the 60 minutes preceding the hour indicated.

Total Sky Cover

Amount of sky dome in tenths covered by clouds or obscuring phenomena at the hour indicated.

Opaque Sky Cover

Amount of sky dome in tenths covered by clouds or obscuring phenomena that prevent observing the sky or higher cloud layers at the hour indicated.

Dry Bulb Temperature

Dry bulb temperature in ° C/° F at the hour indicated.

Dew Point Temperature

Dew point temperature in ° C/° F at the hour indicated.

Relative Humidity

Relative humidity in percent at the hour indicated.

Atmospheric Pressure

Atmospheric pressure at station in lbs per sq. inch at the hour indicated.

Wind Direction

Wind direction in degrees at the hour indicated. (N=0 or 360, E=90, S=180, W=270).
For calm winds, wind direction equals zero.

Wind Speed

Wind speed in mph or m/sec per hour at the hour indicated.

Precipitable Water

Precipitable water in mm or inches at the hour indicated.

Aerosol Optical Depth

Broadband aerosol optical depth (broad-band turbidity) in thousandths on the day indicated.

Humidity Ratio

Humidity ratio in grams/grains of moisture per kg/pound of dry air at the hour

indicated. *This is a calculated value.*

Wet Bulb Temperature

Wet bulb temperature in ° C/° F at the hour indicated. *This is a calculated value.*

Day of Week

Day of Week expressed as an integer (Sunday=1 to Saturday=7)

Enthalpy

Total energy in the air (in kJ/kg or BTU/lb) including both sensible and latent energies, with respect to a standard reference point, (typically zero degrees and zero moisture content). *This is a calculated value.*

These city TMY2 weather data files are included with BinMaker® PRO?	
<u>Alaska</u> Anchorage Annette Barrow Bethel Bettles Big Delta Cold Bay Fairbanks Gulkana King Salmon Kodiak Kotzebue McGrath Nome St. Paul Is. Talkeetna Yakutat	<u>North Carolina</u> Asheville Cape Hatteras Charlotte Greensboro Raleigh Wilmington <u>North Dakota</u> Bismarck Fargo Minot <u>Nebraska</u> Grand Island Norfolk North Platte Omaha Scottsbluff <u>New Hampshire</u> Concord <u>New Jersey</u>

Huntsville
Mobile
Montgomery

Arkansas

Fort Smith
Little Rock

Arizona

Flagstaff
Phoenix
Prescott
Tucson

California

Arcata
Bakersfield
Daggett
Fresno
Long Beach
Los Angeles
Sacramento
San Diego
San Francisco
Santa Maria

Colorado

Alamosa
Boulder
Colorado Springs
Eagle
Grand Junction
Pueblo

Connecticut

Bridgeport
Hartford

Atlantic City
Newark

New Mexico

Albuquerque
Tucumcari

Nevada

Elko
Ely
Las Vegas
Reno
Tonopah
Winnemucca

New York

Albany
Binghamton
Buffalo
Massena
New York City
Rochester
Syracuse

Ohio

Akron
Cleveland
Columbus
Daytona
Mansfield
Toledo
Youngstown

Oklahoma

Oklahoma City
Tulsa

Oregon

Delaware

Wilmington

Florida

Daytona Beach

Jacksonville

Key West

Miami

Tallahassee

Tampa

West Palm Beach

Georgia

Athens

Atlanta

Augusta

Columbus

Macon

Savannah

Hawaii

Hilo

Honolulu

Kahului

Lihue

Iowa

Des Moines

Mason City

Sioux City

Waterloo

Idaho

Boise

Pocatello

Illinois

Chicago

Astoria

Burns

Eugene

Medford

North Bend

Pendleton

Portland

Redmond

Salem

Pennsylvania

Allentown

Bradford

Erie

Harrisburg

Philadelphia

Pittsburgh

Wilkes-Barre

Williamsport

Pacific Islands

Guam

Puerto Rico

San Juan

Rhode Island

Providence

South Carolina

Charleston

Columbia

Greenville

South Dakota

Huron

Pierre

Rapid City

Moline

Peoria

Rockford

Springfield

Indiana

Evansville

Fort Wayne

Indianapolis

South Bend

Kansas

Dodge City

Goodland

Topeka

Wichita

Kentucky

Covington

Lexington

Louisville

Louisiana

Baton Rouge

Lake Charles

New Orleans

Shreveport

Massachusetts

Boston

Worcester

Maryland

Baltimore

Maine

Carlbou

Portland

Michigan

Sioux Falls

Tennessee

Bristol

Chattanooga

Knoxville

Memphis

Nashville

Texas

Abliene

Amarillo

Austin

Brownsville

Corpus Christi

El Paso

Fort Worth

Houston

Lubbock

Lufkin

Midland

Port Arthur

San Angelo

San Antonio

Victoria

Waco

Wichita Falls

Utah Cedar City

Salt Lake City

Virginia

Lynchburg

Norfolk

Richmond

Alpena
Detroit
Flint
Grand Rapids
Houghton
Lansing
Muskegon
Sault Ste. Marie
Traverse City

Minnesota

Duluth
International Falls
Minneapolis
Rochester
Saint Cloud

Missouri

Columbia
Kansas City
Springfield
St. Louis

Mississippi

Jackson
Meridian

Montana

Billings
Cut Bank
Glasgow
Great Falls
Helena
Kalispell
Lewistown

Roanoke
Sterling

Vermont

Burlington

Washington

Olympia
Quillayute
Seattle
Spokane
Yakima

Wisconsin

Eau Claire
Green Bay
La Crosse
Madison
Milwaukee

West Virginia

Charleston
Elkins
Huntington

Wyoming

Casper
Cheyenne
Lander
Rock Springs
Sheridan

Miles City Missoula	
------------------------	--